



**ECO-TEC WATER SYSTEMS**

## **VÁLVULA DE CONTROL MODELO F77AS**



### **Válvula Manual de 5 posiciones para suavizador**

- **Servicio**
- **Retrolavado**
- **Succión de Salmuera**
- **Relleno de tanque de salmuera**
- **Rinse**



## **ECO-TEC WATER SYSTEMS**

### **CARACTERÍSTICAS:**

<b>MATERIAL DE FABRICACIÓN CUERPO:</b>	<b>PLÁSTICO ABS</b>
<b>PRESIÓN MÁXIMA:</b>	<b>85 PSI</b>
<b>TEMPERATURA DE OPERACIÓN:</b>	<b>5-45°C</b>
<b>CAUDAL MÁXIMO:</b>	<b>79 GPM</b>
<b>CONEXIONES I/O:</b>	<b>2"</b>
<b>DRENAJE:</b>	<b>2"</b>
<b>CONECTOR DE SALMUERA</b>	<b>3/4"</b>
<b>TUBO DISTRIBUIDOR:</b>	<b>1 ½"</b>
<b>CONEXIÓN A TANQUE:</b>	<b>4"-8UN</b>
<b>OPCIONES DE MONTAJE:</b>	<b>SUPERIOR Y LATERAL</b>
<b>CERTIFICACIONES:</b>	<b>NSF/ANSI STANDARD 61</b>



**ECO-TEC WATER SYSTEMS**

**NSF International**

RECOGNIZES

Wenzhou Runxin Manufacturing Machine Co., Ltd.  
China

AS COMPLYING WITH NSF/ANSI 61 AND ALL APPLICABLE REQUIREMENTS.  
PRODUCTS APPEARING IN THE NSF OFFICIAL LISTING ARE  
AUTHORIZED TO BEAR THE NSF MARK.



This certificate is the property of NSF International and must be returned upon request. For the most current and complete information, please access NSF's website ([www.nsf.org](http://www.nsf.org)).

August 18, 2010  
Certificate# 4G460 - 01

David Purkiss, General Manager  
Water Distribution Systems