



ECO-TEC WATER SYSTEMS

VÁLVULA DE CONTROL MODELO F64D1



Válvula Manual de 5 posiciones para suavizador

- Servicio
- Retrolavado
- Succión de Salmuera
- Relleno de tanque de salmuera
- Rinse



ECO-TEC WATER SYSTEMS

CARACTERÍSTICAS:

MATERIAL DE FABRICACIÓN CUERPO:	PLÁSTICO ABS
PRESIÓN MÁXIMA:	85 PSI
TEMPERATURA DE OPERACIÓN:	5-45°C
CAUDAL MÁXIMO:	44 GPM
CONEXIONES I/O:	2"
DRENAJE:	1"
CONECTOR DE SALMUERA	1/2"
TUBO DISTRIBUIDOR:	1 ½"
CONEXIÓN A TANQUE:	4"-8UN
OPCIONES DE MONTAJE:	SUPERIOR Y LATERAL
CERTIFICACIONES:	NSF/ANSI STANDARD 61



ECO-TEC WATER SYSTEMS

NSF International

RECOGNIZES

Wenzhou Runxin Manufacturing Machine Co., Ltd.
China

AS COMPLYING WITH NSF/ANSI 61 AND ALL APPLICABLE REQUIREMENTS.
PRODUCTS APPEARING IN THE NSF OFFICIAL LISTING ARE
AUTHORIZED TO BEAR THE NSF MARK.



Certification Program
Accredited by the
American National
Standards Institute



Certification Program
Accredited by the
Standards Council
of Canada

This certificate is the property of NSF International and must be returned upon request. For the most current and complete information, please access NSF's website (www.nsf.org).

August 18, 2010
Certificate# 4G460 - 01

David Purkiss, General Manager
Water Distribution Systems