



VÁLVULA DE CONTROL MODELO F67C1



Válvula de 3 posiciones para filtro

- Servicio
- Retrolavado
- Rinse

Capacidad de programar los retrolavados por tiempo.

Con opciones de programación para señales externas.



ECO-TEC WATER SYSTEMS

CARACTERÍSTICAS:

MATERIAL DE FABRICACIÓN CUERPO:	PLÁSTICO ABS
PRESIÓN MÁXIMA:	85 PSI
CONEXIONES:	100-240V/50-60Hz
TEMPERATURA DE OPERACIÓN:	5-45°C
CAUDAL MÁXIMO:	26 GPM
CONEXIONES I/O:	1"
TUBO DISTRIBUIDOR:	¾"
CONEXIÓN A TANQUE:	2.5" 8UN
OPCIONES DE MONTAJE:	SUPERIOR
CERTIFICACIONES:	NSF/ANSI STANDARD 61
	CE
	RoHS



ECO-TEC WATER SYSTEMS

NSF International

RECOGNIZES

Wenzhou Runxin Manufacturing Machine Co., Ltd.
China

AS COMPLYING WITH NSF/ANSI 61 AND ALL APPLICABLE REQUIREMENTS.
PRODUCTS APPEARING IN THE NSF OFFICIAL LISTING ARE
AUTHORIZED TO BEAR THE NSF MARK.



This certificate is the property of NSF International and must be returned upon request. For the most current and complete information, please access NSF's website (www.nsf.org).

August 18, 2010
Certificate# 4G460 - 01

David Purkiss, General Manager
Water Distribution Systems