



**ECO-TEC WATER SYSTEMS**

## **VÁLVULA DE CONTROL MODELO F75B1**



**Válvula de 3 posiciones para filtro**

- Servicio
- Retrolavado
- Rinse

**Capacidad de programar los retrolavados por tiempo.**

**Con opciones de programación para señales externas.**



## **ECO-TEC WATER SYSTEMS**

### **CARACTERÍSTICAS:**

<b>MATERIAL DE FABRICACIÓN CUERPO:</b>	<b>PLÁSTICO ABS</b>
<b>PRESIÓN MÁXIMA:</b>	<b>85 PSI</b>
<b>CONEXIONES:</b>	<b>100-240V/50-60Hz</b>
<b>TEMPERATURA DE OPERACIÓN:</b>	<b>5-45°C</b>
<b>CAUDAL MÁXIMO:</b>	<b>44 GPM</b>
<b>CONEXIONES I/O:</b>	<b>2"</b>
<b>DRENAJE:</b>	<b>2"</b>
<b>TUBO DISTRIBUIDOR:</b>	<b>1 1/2"</b>
<b>CONEXIÓN A TANQUE:</b>	<b>4"-8UN</b>
<b>OPCIONES DE MONTAJE:</b>	<b>SUPERIOR</b>
<b>CERTIFICACIONES:</b>	<b>NSF/ANSI STANDARD 61</b>
	<b>CE</b>
	<b>RoHS</b>



**ECO-TEC WATER SYSTEMS**

## NSF International

RECOGNIZES

Wenzhou Runxin Manufacturing Machine Co., Ltd.  
China

AS COMPLYING WITH NSF/ANSI 61 AND ALL APPLICABLE REQUIREMENTS.  
PRODUCTS APPEARING IN THE NSF OFFICIAL LISTING ARE  
AUTHORIZED TO BEAR THE NSF MARK.



This certificate is the property of NSF International and must be returned upon request. For the most current and complete information, please access NSF's website ([www.nsf.org](http://www.nsf.org)).

August 18, 2010  
Certificate# 4C460 - 01

David Purkiss, General Manager  
Water Distribution Systems