

Model 110 & 120 Chlorinator/Dechlorinator

ITEM	PART NUMBER
Model 110 Chlorinator/Dechlorinator	110
Model 120 Chlorinator/Dechlorinator	120

MODEL 110 CHLORINATOR/DECHLORINATOR:

This durable and reliable commercial chlorinator is capable of disinfecting flows up to 50,000 gpd and up to 100,000 gpd when installed in parallel. The maximum flow rate on the Model 110 is 80 gpm (gallons per minute) and 160 gpm when installed in parallel. This unit has a 6 5/8" diameter inlet.

MODEL 120 CHLORINATOR/DECHLORINATOR:

This durable and reliable commercial chlorinator is capable of disinfection flows up to 50,000 gpd and up to 100,000 gpd when installed in parallel. The maximum flow rate on the model 120 is 80 gpm and 160 gpm when installed in parallel. Inlet diameter is variable up to 10".

Both models come equipped with the following:

FEATURES

- **MOUNTING** - each comes equipped with an easy mounting base for easy installation in a chlorine contact chamber
- **MATERIALS** - each is constructed with high density polyethylene, which is chemical and ultraviolet resistant
- **FEED TUBES** - each model contains 4-22 5/8" PVC tubes with a 3" inside diameter and caps. Each tube can hold 27 tablets
- **OUTLET WEIR PLATES** - three outlet weir plates ranging from 1" to 3" are included to regulate effluent level. Each plate is calibrated with Metric and English to enable the user to visually determine the flow rate
- **INLET BAFFLE** - Controls the direction and velocity of flow within the tablet feeder
- **LIMITED WARRANTY** - Every tablet feeder carries a 10-year limited warranty against defective material and workmanship

