

# **Residential Ozone Generator**

Mini Ozone Generator FM-300	)	
BEYOK OZONE	Ozone Output:	200 mg/hr on ambient air, 300 mg/hr on dry air
	Pump Output:	4~6 SCFH (2~3 lpm)
	Pump Pressure:	2 PSI (14 KPa)
	Generating Method:	Corona Discharge (corona tube)
	Electrical:	220V/50Hz-120V/60Hz available,10W
	Control:	1-60min adjustable timer
	Air inlet & outlet Dia:	1/4" barb (6mm)
	Power Cable:	4-ft (1.2m) in length
	Case:	Plastic
	Accessories:	2 sets of 4-ft tube & diffuser stone
	Dimension(LxWxH):	5.6" x 3.9" x 1.7" (143x 99 x43mm)
	Net Weight:	1.4-lb (0.65 kg)

The BEYOKozone FM- series ozone generators are highly integrated corona discharge three in one units with ozone tube, ozone power and air pump in one plastic case (FM-300SNP without air pump). They have been used as a functional unit for residential air sterilizers and for water treatment, including applying to spas, baths, small pools and anywhere small volume of water sterilizing.

They are very compact design but are very powerful and enduring product.

### **Features:**

- Compact design with high performance air pump
- Ready to use upon delivery
- Able to connect with air dryer through air inlet to increase ozone output
- Low power consumption
- Safe, quiet and energy efficient
- One year warranty with CE marked

#### **Benefits:**

- · Eliminates odors, freshens air
- Destroys airborne microbes
- Drinking water purification
- Food preservation

## **Application:**

- Kitchen, laundry room, bathroom, refrigerator
- School, hotel, entertainment
- Fruit, vegetable and meat detoxification
- Ornamental water features

## Size View:

